



Safety Data Sheet

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: 260 GT With Ethanol

Manufacturer Information:

Sunoco, Inc. (R&M)
1735 Market Street LL

Philadelphia, Pennsylvania, 19103-7583
sunocomsds@sunocoinc.com

Product Use:

Motor Fuel
California Air Resources Board (CARB):
This product cannot be sold, offered for sale,
supplied or offered for supply for motor
vehicles in California except in competition
racing vehicles. Legal For Use ONLY
in Competition Racing Vehicles.
Not Legal For Use in Any Other Motor Vehicle.

Emergency Phone Numbers:

Chemtrec	(800) 424-9300	24 Hours
Sunoco Inc.	(800) 964-8861	24 Hours

Information:

Product Safety Information	(888) 567-3066
----------------------------	----------------

2. HAZARDS IDENTIFICATION

- EMERGENCY OVERVIEW**

Danger! Extremely flammable liquid and vapor. Static accumulator. May form an ignitable vapor/air mixture. Vapors may cause flash fire or explosion. Excessive exposure to mists or vapors generated by heat may cause irritation to eyes, nose, throat, lungs and respiratory tract. Harmful or fatal if swallowed. Pulmonary aspiration hazard. While ingesting or vomiting, may enter lungs and produce damage. Harmful if inhaled. Overexposure may lead to serious disturbances of heart rhythm and nervous system effects, including drowsiness, dizziness, nausea, headaches, paralysis, loss of consciousness and even death. May cause skin irritation. May cause eye irritation. Contains material or materials that can cause cancer. Contains material or materials that may cause birth defects. May cause target organ or system damage to the following: central nervous system, eye, kidney, liver, respiratory system, skin, blood, cardiovascular system, heart, peripheral nervous system, bone marrow,

Hazards Ratings:

Key: 0 = least, 1 = slight, 2 = moderate, 3 = high, 4 = extreme

	<u>Health</u>	<u>Fire</u>	<u>Reactivity</u>	<u>PPI</u>
NFPA	1	3	0	
HMIS	2	3	0	X

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No.	Amount (Vol%)
ISOOCTANE	26635-64-3	30 - 70
TOLUENE	108-88-3	5 - 25
ALKYLATE	64741-66-8	5 - 20
ISOPENTANE	78-78-4	5 - 15
ETHYL ALCOHOL	64-17-5	7 - 10
BUTANE	106-97-8	0 - 5
XYLENE	1330-20-7	0.001 - 0.01
N-HEXANE	110-54-3	0.001 - 0.01
ETHYL BENZENE	100-41-4	0.001 - 0.01
CYCLOPENTANE	287-92-3	0.001 - 0.01
BENZENE	71-43-2	0.002 - 0.01

4. FIRST AID MEASURES

- INHALATION**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and continue to monitor. Get immediate medical attention. NOTE TO PHYSICIAN: Catecholamines and similar adrenergic drugs are generally contraindicated because of potential for increased sensitivity of the heart from hydrocarbon overexposure and subsequent ventricular fibrillation. EKG monitoring may be indicated and bronchodilators should be selected with care.

- SKIN**

Immediately flush with large amounts of water for 20 minutes, use soap if available. Remove contaminated clothing, including shoes, after flushing has begun. Get prompt medical attention. Wash clothing before reuse. NOTE TO PHYSICIAN: Following injection, prompt debridement of the wound is necessary to minimize necrosis and tissue loss.

- EYES**

Flush eye with water for 20 minutes. Get medical attention.

- INGESTION**

If swallowed, immediately contact a physician or Poison Control Center. Never give anything by mouth to an intoxicated, unconscious or convulsing person. Get immediate medical attention. Do not induce vomiting!

5. FIRE FIGHTING MEASURES

- EXTINGUISHING MEDIA**

The following media may be used to extinguish a fire involving this material: Water spray; Regular foam; Dry chemical; Carbon dioxide;

- FIRE FIGHTING INSTRUCTIONS**

Use water spray to cool fire exposed tanks and containers. Wear structural fire fighting gear. The use of fresh air equipment such as Self Contained Breathing Apparatus (SCBA) or Supplied Air Respirators should be worn for fire fighting if exposure or potential exposure to products of combustion is expected.

FLAMMABLE PROPERTIES

	Typical	Minimum	Maximum	Text Result	Units	Method
Flash Point				MINUS 40 EST'D	F	N/A
Autoignition Temperature				536 ESTIMATED	F	N/A
Lower Explosion Limit	1.5				%	N/A
Upper Explosion Limit	7.6				%	N/A

6. ACCIDENTAL RELEASE MEASURES

Prevent ignition, stop leak and ventilate the area. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste

container. Do not use spark-generating metals for sweeping up spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Vapor can be controlled using a water fog. Water streams should not be directed to the liquid as this will cause the liquid to boil and generate more vapor. Keep personnel upwind from leak. Use appropriate personal protective equipment as stated in Section 8 of this MSDS. Advise the Environmental Protection Agency (EPA) and appropriate state agencies, if required.

7. HANDLING AND STORAGE

- **HANDLING**

Follow all MSDS/label precautions even after container is emptied because it may retain product residue. Use only in a well-ventilated area. **STATIC ACCUMULATOR.** This liquid may form an ignitable vapor-air mixture in closed tanks or containers. This liquid may accumulate static electricity even when transferred into properly grounded containers. Bonding and grounding may be insufficient to remove static electricity. Static electricity accumulation may be significantly increased by the presence of small quantities of water. Always bond receiving container to the fill pipe before and during loading, following NFPA-77 and/or API RP 2003 requirements. Automatic gauging devices and other floats in vessels or tanks which contain static accumulating liquids should be electrically bonded to the shell. Bonding and grounding alone may be inadequate to eliminate fire and explosion hazards associated with electrostatic charges. In addition to bonding and grounding, efforts to mitigate the hazards of an electrostatic discharge may include, but are not limited to, ventilation, inerting and/or reduction of transfer velocities. Always keep the nozzle in contact with the container throughout the loading process. Do not fill any portable containers in or on a vehicle. Special precautions, such as reduced loading rates and increased monitoring, must be observed during "switch loading" operations (i.e. loading this material in tanks or shipping compartments that previously contained middle distillates or similar products). Non-equilibrium conditions may increase the risks associated with static electricity such as tank and container filling, tank cleaning, sampling, gauging, loading, filtering, mixing, agitation, etc. Dissipation of electrostatic charges may be improved with the use of conductivity additives when used with other mitigating efforts, including bonding and grounding. Avoid breathing (dust, vapor, mist, gas). Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Never siphon by mouth. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.** Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioned, or properly disposed of. A static electrical discharge can accumulate when this material is flowing through pipes, nozzles or filters or when it is agitated. A static spark discharge can ignite accumulated vapors particularly during dry weather. Always bond receiving containers to the fill pipe before and during loading. Always keep nozzle in contact with the container throughout the loading process. Do not fill any portable container in or on the vehicle.

- **STORAGE**

Keep away from heat, sparks, and flame. Keep container closed when not in use. Store in a cool dry place. Consult NFPA and / or OSHA codes for additional information. NFPA class IB storage. Flash point is less than 73 degrees F and boiling point is greater than or equal to 100 degrees F. Outside or detached storage is preferred.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Consult With a Health and Safety Professional for Specific Selections

- **ENGINEERING CONTROLS**

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use with adequate ventilation. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

- **PERSONAL PROTECTION**

- **EYE PROTECTION**

Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

- **GLOVES or HAND PROTECTION**

The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Protective gloves are recommended to protect against contact with product. Nitrile; Viton; Teflon;

RESPIRATORY PROTECTION

Concentration in air determines the level of respiratory protection needed. Use only NIOSH certified respiratory equipment. Half-mask air purifying respirator with organic vapor cartridges is acceptable for exposures to ten (10) times the exposure limit. Full-face air purifying respirator with organic vapor cartridges is acceptable for exposures to fifty (50) times the exposure limit. Exposure should not exceed the cartridge limit of 1000 ppm. Protection by air purifying respirators is limited. Use a positive pressure-demand full-face supplied air respirator or SCBA for exposures greater than fifty (50) times the exposure limit. If exposure is above the IDLH (Immediately Dangerous to Life and Health) or there is the possibility of an uncontrolled release, or exposure levels are unknown, then use a positive pressure-demand full-face supplied air respirator with escape bottle or SCBA. Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

OTHER

Where splashing is possible, full chemically resistant protective clothing and boots are required. The following materials are acceptable for use as protective clothing: Nitrile; Viton; Teflon; Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Remove contaminated clothing and wash before reuse. For non-fire emergencies, positive pressure SCBA and structural firefighter's protective clothing will provide only limited protection.

EXPOSURE GUIDELINES (SEE SECTION 15 FOR ADDITIONAL EXPOSURE LIMITS)

	CAS No.	Governing Body	Exposure Limits		
ALKYLATE	64741-66-8	Sunoco	TWA	100	ppm
BENZENE	71-43-2	ACGIH	STEL	2.5	ppm
BENZENE	71-43-2	OSHA	STEL	5	ppm
BENZENE	71-43-2	ACGIH	TWA	0.5	ppm
BENZENE	71-43-2	OSHA	TWA	1	ppm
BUTANE	106-97-8	ACGIH	TWA	1000	ppm
ETHYL ALCOHOL	64-17-5	ACGIH	TWA	1000	ppm
ETHYL ALCOHOL	64-17-5	OSHA	TWA	1000	ppm
ETHYL BENZENE	100-41-4	ACGIH	TWA	20	ppm
ETHYL BENZENE	100-41-4	OSHA	TWA	100	ppm
ISOPENTANE	78-78-4	Sunoco	STEL	750	ppm
ISOPENTANE	78-78-4	ACGIH	TWA	600	ppm
ISOPENTANE	78-78-4	Sunoco	TWA	600	ppm
N-HEXANE	110-54-3	ACGIH	TWA	50	ppm
N-HEXANE	110-54-3	OSHA	TWA	500	ppm
TOLUENE	108-88-3	NIOSH	STEL	150	ppm
TOLUENE	108-88-3	ACGIH	TWA	20	ppm
TOLUENE	108-88-3	OSHA	TWA	200	ppm
XYLENE	1330-20-7	ACGIH	STEL	150	ppm
XYLENE	1330-20-7	ACGIH	TWA	100	ppm
XYLENE	1330-20-7	OSHA	TWA	100	ppm
CYCLOPENTANE	287-92-3	ACGIH	TWA	600	ppm

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Property	Typical	Units	Text Result	Reference
Appearance		N/A	CLEAR LIQUID.	
Boiling Point		F	100 - 260	
Bulk Density		lb/gal	no data	
Melting Point		F	no data	
Molecular Weight		g/mole	no data	
Octanol/Water Coefficient		N/A	no data	
pH		N/A	no data	
Specific Gravity	0.76	N/A		
Solubility In Water		wt %	NIL TO 15%	

Odor		N/A	GASOLINE ODOR.	
Odor Threshold		ppm	< 1	
Vapor Pressure		psia	5 - 16	
Viscosity (F)		SUS	no data	
Viscosity (C)		CsT	no data	
% Volatile	100	wt %		

10. STABILITY AND REACTIVITY

- **STABILITY**

Stable

- **CONDITIONS TO AVOID**

Avoid heat, sparks and open flame. Avoid static discharge.

- **INCOMPATIBILITY**

The following materials are incompatible with this product: Strong oxidizers Alkaline materials; Acids; Chlorine; Concentrated oxygen; Halogens and halogenated compounds; Hydrogen peroxide;

- **HAZARDOUS DECOMPOSITION PRODUCTS**

Combustion may produce carbon monoxide, carbon dioxide and other asphyxiants.

- **HAZARDOUS POLYMERIZATION**

Will not polymerize.

11. TOXICOLOGY INFORMATION

Single Exposure Health Effects

Oral:

LD50 (g/kg): no data

Dermal:

LD50 (mg/kg): no data

Inhalation:

LC50 (mg/l): no data

LC50 (mg/m3): no data

LC50 (ppm): no data

- **POTENTIAL HEALTH EFFECTS**

- **INHALATION**

High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness and even death). May cause serious disturbances of heart rhythm. Excessive exposure to mists or vapors generated by heat may cause irritation to eyes, nose, throat, lungs and respiratory tract. Solvent "huffing/sniffing" (abuse) or intentional prolonged overexposure to high levels of vapors can produce abnormal behavior, convulsions, hallucinations, delirium, nervous system damage, serious disturbances of heart rhythm and sudden death. Repeated excessive exposures may cause blood disorders such as anemia and leukemia. Contains a material that has been related to cancer in humans. See Section 15 for additional information.

- **SKIN**

Moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

- **EYES**

Moderately irritating to the eyes. Contact with the eye may cause redness, burning, tearing and/or blurred vision.

- **INGESTION**

Harmful or fatal if swallowed. Pulmonary aspiration hazard. While ingesting or vomiting, may enter lungs and produce damage. Irritating to mouth, throat, and stomach. May produce central nervous system effects, which includes dizziness, loss of balance and coordination, unconsciousness, coma and even death. Contains material or materials that can cause birth defects.

- **PRE-EXISTING MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

The following diseases or disorders may be aggravated by exposure to this product: skin, eye, blood forming organs, nervous system, respiratory system, lung (asthma-like conditions), cardiovascular system, liver, kidney,

Additional Toxicology Information

No data available

Component Toxicity Information

Ethylbenzene, a component of this product, has been designated by the International Agency for Research on Cancer as "possibly carcinogenic to humans", based on increased tumor incidence in laboratory animals. Overexposure may lead to nervous system effects, including drowsiness, dizziness, nausea, headaches, paralysis, loss of consciousness and even death. Repeated overexposure has caused a hearing loss in laboratory animals. Prolonged and repeated excessive exposures to benzene can result in blood disorders ranging from anemia to leukemia. Hours of exposure to high airborne concentrations of toluene and xylene, minor components of this product, has caused a hearing loss in laboratory animals.

12. ECOLOGICAL INFORMATION

Gasoline spills are toxic to fish and aquatic flora.

13. DISPOSAL CONSIDERATIONS

Follow federal, state and local regulations. This material is a RCRA hazardous waste. Do not flush material to drain or storm sewer. Contract to authorized disposal service.

14. TRANSPORT INFORMATION

<u>Governing Body</u>	<u>Mode</u>	<u>Proper Shipping Name</u>
DOT	Ground	Gasohol

<u>Governing Body</u>	<u>Mode</u>	<u>Hazard Class</u>	<u>UN/NA No.</u>	<u>Label</u>
DOT	Ground	3 (Flammable liquid)	NA1203	

15. REGULATORY INFORMATION

This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372): Maximum Wt%: Toluene- CAS Number 108-88-3, 25 % The remaining Sara 313 components listed in Section 14 of the MSDS are less than the reported de minimis levels. This information must be included in all MSDSs that are copied and distributed for this material.

<u>Regulatory List</u>	<u>Component</u>	<u>CAS No.</u>
ACGIH - Occupational Exposure Limits - Carcinogens	BENZENE	71-43-2
ACGIH - Occupational Exposure Limits - Carcinogens	ETHYL ALCOHOL	64-17-5
ACGIH - Occupational Exposure Limits - Carcinogens	ETHYL BENZENE	100-41-4
ACGIH - Occupational Exposure Limits - Carcinogens	TOLUENE	108-88-3

ACGIH - Occupational Exposure Limits - Carcinogens
 ACGIH - Occupational Exposure Limits - TWAs
 ACGIH - Occupational Exposure Limits - TWAs
 ACGIH - Occupational Exposure Limits - TWAs
 ACGIH - Occupational Exposure Limits - TWAs
 ACGIH - Occupational Exposure Limits - TWAs
 ACGIH - Occupational Exposure Limits - TWAs
 ACGIH - Occupational Exposure Limits - TWAs
 ACGIH - Occupational Exposure Limits - TWAs
 ACGIH - Short Term Exposure Limits
 ACGIH - Short Term Exposure Limits
 ACGIH - Short Term Exposure Limits
 ACGIH - Short Term Exposure Limits
 ACGIH - Skin Absorption Designation
 ACGIH - Skin Absorption Designation
 CAA (Clean Air Act) - HON Rule - Organic HAPs
 CAA (Clean Air Act) - HON Rule - Organic HAPs
 CAA (Clean Air Act) - HON Rule - Organic HAPs
 CAA (Clean Air Act) - HON Rule - Organic HAPs
 CAA (Clean Air Act) - HON Rule - Organic HAPs
 CAA (Clean Air Act) - HON Rule - SOCMI Chemicals
 CAA (Clean Air Act) - HON Rule - SOCMI Chemicals
 CAA (Clean Air Act) - HON Rule - SOCMI Chemicals
 CAA (Clean Air Act) - HON Rule - SOCMI Chemicals
 CAA (Clean Air Act) - HON Rule - SOCMI Chemicals
 CAA - 1990 Hazardous Air Pollutants
 CAA - 1990 Hazardous Air Pollutants
 CAA - 1990 Hazardous Air Pollutants
 CAA - 1990 Hazardous Air Pollutants
 CAA - 1990 Hazardous Air Pollutants
 California - Prop. 65 - Developmental Toxicity
 California - Prop. 65 - Developmental Toxicity
 California - Prop. 65 - Developmental Toxicity
 California - Prop. 65 - Reproductive - Female
 California - Prop. 65 - Reproductive - Male
 California - Proposition 65 - Carcinogens List
 California - Proposition 65 - Carcinogens List
 Canada - WHMIS - Ingredient Disclosure
 Canada - WHMIS - Ingredient Disclosure
 Canada - WHMIS - Ingredient Disclosure
 Canada - WHMIS - Ingredient Disclosure
 Canada - WHMIS - Ingredient Disclosure
 Canada - WHMIS - Ingredient Disclosure
 CERCLA/SARA - Haz Substances and their RQs
 CERCLA/SARA - Haz Substances and their RQs
 CERCLA/SARA - Haz Substances and their RQs
 CERCLA/SARA - Haz Substances and their RQs
 CERCLA/SARA - Haz Substances and their RQs
 CERCLA/SARA - Section 313 - Emission Reporting
 CERCLA/SARA - Section 313 - Emission Reporting
 CERCLA/SARA - Section 313 - Emission Reporting
 CERCLA/SARA - Section 313 - Emission Reporting
 CERCLA/SARA - Section 313 - Emission Reporting
 CWA (Clean Water Act) - Hazardous Substances
 CWA (Clean Water Act) - Hazardous Substances
 CWA (Clean Water Act) - Hazardous Substances
 CWA (Clean Water Act) - Hazardous Substances
 CWA (Clean Water Act) - Priority Pollutants
 CWA (Clean Water Act) - Priority Pollutants
 CWA (Clean Water Act) - Priority Pollutants
 CWA (Clean Water Act) - Toxic Pollutants
 CWA (Clean Water Act) - Toxic Pollutants

XYLENE	1330-20-7
BENZENE	71-43-2
BUTANE	106-97-8
CYCLOPENTANE	287-92-3
ETHYL BENZENE	100-41-4
ISOPENTANE	78-78-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
XYLENE	1330-20-7
BENZENE	71-43-2
N-HEXANE	110-54-3
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
ETHYL ALCOHOL	64-17-5
TOLUENE	108-88-3
TOLUENE	108-88-3
BENZENE	71-43-2
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
BUTANE	106-97-8
CYCLOPENTANE	287-92-3
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
ETHYL BENZENE	100-41-4
TOLUENE	108-88-3
BENZENE	71-43-2
ETHYL BENZENE	100-41-4

CWA (Clean Water Act) - Toxic Pollutants
IARC - Group 1 (carcinogenic to humans)
IARC - Group 1 (carcinogenic to humans)
IARC - Group 2B (Possibly carcinogenic to humans)
IARC - Group 3 (not classifiable)
IARC - Group 3 (not classifiable)
Inventory - Australia (AICS)
Inventory - Australia (AICS)
Inventory - Australia (AICS)
Inventory - Australia (AICS)
Inventory - Australia (AICS)
Inventory - Australia (AICS)
Inventory - Australia (AICS)
Inventory - Australia (AICS)
Inventory - Australia (AICS)
Inventory - Australia (AICS)
Inventory - Australia (AICS)
Inventory - Canada - Domestic Substances List
Inventory - Canada - Domestic Substances List
Inventory - Canada - Domestic Substances List
Inventory - Canada - Domestic Substances List
Inventory - Canada - Domestic Substances List
Inventory - Canada - Domestic Substances List
Inventory - Canada - Domestic Substances List
Inventory - Canada - Domestic Substances List
Inventory - Canada - Domestic Substances List
Inventory - Canada - Domestic Substances List
Inventory - Canada - Domestic Substances List
Inventory - Canada - Domestic Substances List
Inventory - Canada - Non-Domestic Substances List
Inventory - China
Inventory - China
Inventory - China
Inventory - China
Inventory - China
Inventory - China
Inventory - China
Inventory - China
Inventory - China
Inventory - China
Inventory - European EINECS Inventory
Inventory - European EINECS Inventory
Inventory - European EINECS Inventory
Inventory - European EINECS Inventory
Inventory - European EINECS Inventory
Inventory - European EINECS Inventory
Inventory - European EINECS Inventory
Inventory - European EINECS Inventory
Inventory - European EINECS Inventory
Inventory - European EINECS Inventory
Inventory - Japan - (ENCS)
Inventory - Japan - (ENCS)
Inventory - Japan - (ENCS)
Inventory - Japan - (ENCS)
Inventory - Japan - (ENCS)
Inventory - Japan - (ENCS)
Inventory - Japan - (ENCS)
Inventory - Japan - (ENCS)
Inventory - Japan - (ENCS)
Inventory - Japan - (ENCS)
Inventory - Korea - Existing and Evaluated
Inventory - Korea - Existing and Evaluated
Inventory - Korea - Existing and Evaluated

TOLUENE	108-88-3
BENZENE	71-43-2
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
TOLUENE	108-88-3
XYLENE	1330-20-7
ALKYLATE	64741-66-8
BENZENE	71-43-2
BUTANE	106-97-8
CYCLOPENTANE	287-92-3
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
ISOOCTANE	26635-64-3
ISOPENTANE	78-78-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
ALKYLATE	64741-66-8
BENZENE	71-43-2
BUTANE	106-97-8
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
ISOOCTANE	26635-64-3
ISOPENTANE	78-78-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
ISOOCTANE	26635-64-3
ALKYLATE	64741-66-8
BENZENE	71-43-2
BUTANE	106-97-8
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
ISOOCTANE	26635-64-3
ISOPENTANE	78-78-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
ALKYLATE	64741-66-8
BENZENE	71-43-2
BUTANE	106-97-8
CYCLOPENTANE	287-92-3
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
ISOOCTANE	26635-64-3
ISOPENTANE	78-78-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
BUTANE	106-97-8
CYCLOPENTANE	287-92-3
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
ISOOCTANE	26635-64-3
ISOPENTANE	78-78-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
ALKYLATE	64741-66-8
BENZENE	71-43-2
BUTANE	106-97-8

Inventory - Korea - Existing and Evaluated
 Inventory - Korea - Existing and Evaluated
 Inventory - Korea - Existing and Evaluated
 Inventory - Korea - Existing and Evaluated
 Inventory - Korea - Existing and Evaluated
 Inventory - Korea - Existing and Evaluated
 Inventory - Korea - Existing and Evaluated
 Inventory - Korea - Existing and Evaluated
 Inventory - Philippines Inventory (PICCS)
 Inventory - Philippines Inventory (PICCS)
 Inventory - Philippines Inventory (PICCS)
 Inventory - Philippines Inventory (PICCS)
 Inventory - Philippines Inventory (PICCS)
 Inventory - Philippines Inventory (PICCS)
 Inventory - Philippines Inventory (PICCS)
 Inventory - Philippines Inventory (PICCS)
 Inventory - Philippines Inventory (PICCS)
 Inventory - Philippines Inventory (PICCS)
 Inventory - TSCA - Sect. 8(b) Inventory
 Inventory - TSCA - Sect. 8(b) Inventory
 Inventory - TSCA - Sect. 8(b) Inventory
 Inventory - TSCA - Sect. 8(b) Inventory
 Inventory - TSCA - Sect. 8(b) Inventory
 Inventory - TSCA - Sect. 8(b) Inventory
 Inventory - TSCA - Sect. 8(b) Inventory
 Inventory - TSCA - Sect. 8(b) Inventory
 Inventory - TSCA - Sect. 8(b) Inventory
 Massachusetts - Right To Know List
 Massachusetts - Right To Know List
 Massachusetts - Right To Know List
 Massachusetts - Right To Know List
 Massachusetts - Right To Know List
 Massachusetts - Right To Know List
 Massachusetts - Right To Know List
 Massachusetts - Right To Know List
 Massachusetts - Right To Know List
 New Jersey - Department of Health RTK List
 New Jersey - Department of Health RTK List
 New Jersey - Department of Health RTK List
 New Jersey - Department of Health RTK List
 New Jersey - Department of Health RTK List
 New Jersey - Department of Health RTK List
 New Jersey - Department of Health RTK List
 New Jersey - Department of Health RTK List
 New Jersey - Department of Health RTK List
 New Jersey - Env Hazardous Substances List
 New Jersey - Env Hazardous Substances List
 New Jersey - Env Hazardous Substances List
 New Jersey - Env Hazardous Substances List
 New Jersey - Env Hazardous Substances List
 New Jersey - Env Hazardous Substances List
 New Jersey - Env Hazardous Substances List
 New Jersey - Special Hazardous Substances
 New Jersey - Special Hazardous Substances
 New Jersey - Special Hazardous Substances
 New Jersey - Special Hazardous Substances
 New Jersey - Special Hazardous Substances
 New Jersey - Special Hazardous Substances

CYCLOPENTANE	287-92-3
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
ISOOCTANE	26635-64-3
ISOPENTANE	78-78-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
ALKYLATE	64741-66-8
BENZENE	71-43-2
BUTANE	106-97-8
CYCLOPENTANE	287-92-3
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
ISOOCTANE	26635-64-3
ISOPENTANE	78-78-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
ALKYLATE	64741-66-8
BENZENE	71-43-2
BUTANE	106-97-8
CYCLOPENTANE	287-92-3
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
ISOOCTANE	26635-64-3
ISOPENTANE	78-78-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
BUTANE	106-97-8
CYCLOPENTANE	287-92-3
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
ISOPENTANE	78-78-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
BUTANE	106-97-8
CYCLOPENTANE	287-92-3
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
ISOPENTANE	78-78-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
BUTANE	106-97-8
CYCLOPENTANE	287-92-3
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
ISOPENTANE	78-78-4
N-HEXANE	110-54-3
TOLUENE	108-88-3
XYLENE	1330-20-7
BENZENE	71-43-2
BUTANE	106-97-8
CYCLOPENTANE	287-92-3
ETHYL ALCOHOL	64-17-5
ETHYL BENZENE	100-41-4
ISOPENTANE	78-78-4
N-HEXANE	110-54-3

New Jersey - Special Hazardous Substances	TOLUENE	108-88-3
New Jersey - Special Hazardous Substances	XYLENE	1330-20-7
NTP - Report on Carcinogens - Known Carcinogens	BENZENE	71-43-2
OSHA - Final PELs - Ceiling Limits	BENZENE	71-43-2
OSHA - Final PELs - Ceiling Limits	TOLUENE	108-88-3
OSHA - Final PELs - Short Term Exposure Limits	BENZENE	71-43-2
OSHA - Final PELs - Time Weighted Averages	BENZENE	71-43-2
OSHA - Final PELs - Time Weighted Averages	ETHYL ALCOHOL	64-17-5
OSHA - Final PELs - Time Weighted Averages	ETHYL BENZENE	100-41-4
OSHA - Final PELs - Time Weighted Averages	N-HEXANE	110-54-3
OSHA - Final PELs - Time Weighted Averages	TOLUENE	108-88-3
OSHA - Final PELs - Time Weighted Averages	XYLENE	1330-20-7
Pennsylvania - RTK (Right to Know) List	BENZENE	71-43-2
Pennsylvania - RTK (Right to Know) List	BUTANE	106-97-8
Pennsylvania - RTK (Right to Know) List	CYCLOPENTANE	287-92-3
Pennsylvania - RTK (Right to Know) List	ETHYL ALCOHOL	64-17-5
Pennsylvania - RTK (Right to Know) List	ETHYL BENZENE	100-41-4
Pennsylvania - RTK (Right to Know) List	ISOOCTANE	26635-64-3
Pennsylvania - RTK (Right to Know) List	ISOPENTANE	78-78-4
Pennsylvania - RTK (Right to Know) List	N-HEXANE	110-54-3
Pennsylvania - RTK (Right to Know) List	TOLUENE	108-88-3
Pennsylvania - RTK (Right to Know) List	XYLENE	1330-20-7
Pennsylvania - RTK - Special Hazardous Substances	BENZENE	71-43-2

Title III Classifications Sections 311,312:

- Acute: **YES**
- Chronic: **YES**
- Fire: **YES**
- Reactivity: **NO**
- Sudden Release of Pressure: **NO**

16. OTHER INFORMATION

Follow all MSDS/label precautions even after container is emptied because it may retain product residue. Keep out of reach of children. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner or properly disposed of. Precautionary labeling for pumps, portable containers, and drums is required. A "hazardous when empty" pictogram and D.O.T. flammable liquid label are also required for drums. Details available upon request. Sun recommends that exposures to benzene be kept below 0.5 ppm for 8-hours; 2.5 ppm for 15-min. Normal service station operations are below these values. For use as racing fuel only. Do not use for any other purpose.